Rec'd PCT/PTO 25 APR 2005

JET INJECTOR WITH A BI-STABLE SPRING   10/532521

PCT / GB 02 / 02633 describes a jet injector in which there is a rigid tube terminating

at one end in a nozzle and at the other in a constriction which leads to the main drug

supply. A portion of the rigid tube is formed as a flexible window. There is an over

centre spring and an end thrust beam which may compress the window to cause a high

5   speed flow through the nozzle. The device suffers a number of problems. Priming

the pump is unstable, the spring acting in tension stores insufficient energy, the

flexible window tears from its mount and causes inefficient energy transfer, the spring

and beams carry insufficient momentum, the nozzle form tends to close the entrance

to the track through the skin and energising by pressing against the skin of the patient

10   is somewhat uncomfortable. The present specification details radical improvements

to the device

According to the present invention, there is an injector comprising a rigid tube with an

outlet at one end and a non-return valve at the other end, a hole in the tube wall, an

15   elastomeric liner within the rigid tube and a piston arranged to impact the elastomeric

liner through the hole in the tube to produce a high pressure transient. The injector

includes a spring member arranged to act upon the piston to cause the piston to impact

the liner. The piston is attached to a mass which is capable of being accelerated by

the spring member. The spring member is bi-stable. It may be manually energised to

20   a latched position and may then be triggered by pressure against the skin of a patient.

The spring member comprises an arcuate lamina which is deformable by bending to

decrease in curvature. One end of the spring member is pivotable in a transverse

channel of the rigid tube. The other end of the spring member is connected to the

mass. The mass may be triangularly shaped. An apex of the triangularly shaped mass

25   is pivotable in a retaining groove of the rigid tube. The mass bears the piston which

CONFIRMATION COPY

fits within the hole in the rigid tube for impacting the elastomeric liner. The

elastomeric liner is oversize or axially compressed to provide a seal within the rigid

tube. The elastomeric liner may be axially compressed between a shoulder within the

rigid tube and an oversize plug which comprises a channel and is retained by friction

5   therewithin. The plug may be a cylinder comprising one or more flats or a helical

groove, such that the fit of the plug within the bore of the tube defines one or more

capillary feed channels. The walls of the compressed elastomeric liner may cover the

capillary channels formed by the flats or helical groove, to form a non-return valve

biased in the closed position. Alternatively, the plug may be an oversize capillary

10   tube which retains or compresses the elastomeric liner and is itself retained by

frictional forces. The injector may include a blind elastomeric tube with a transverse

slot off-axis, which forms a non-return valve with the retaining capillary tube. A

conical cross-section of the blind termination of the elastomeric tube may bias the

valve into a closed position. The capillary tube may be sharpened to pierce the

15   rubber septum of an ampoule, to provide a supply of liquid drug to the tube. The

elastomeric liner is preferably made of silicone rubber. The silicone rubber may be

filled with a proportion of silicone oil to provide intrinsic lubrication. The injector

outlet may be a nozzle and the surface surrounding the outlet may be saddle-shaped.

The cross-section of the saddle-shaped outlet is preferably rectangular. The cross-

20   section of the saddle-shaped outlet may increase in size with distance from the axis

thereof. The injector may include a retractor spring which partially removes the

piston from the hole in the rigid tube wall, when the injector is in its quiescent state,

so that the elastomeric liner does not take a compression set. The retractor spring is

preferably low rate and does not retract the piston beyond a given point, such that the

elastomeric liner is not extruded through the hole in the rigid tube wall by pressure

from an associated injection syringe, in use.

The present injector comprises a rigid plastic tube with a nozzle at one end and a

5   transverse hole through the tube wall. The tube contains a tubular liner of silicone

rubber which is retained between a shoulder within the tube and an interference fit

plug inserted into the end of the tube. The liner and hole are in register and

compression of the liner between shoulder and plug ensures a water tight seal. The

plug and liner are so fashioned that they form both a non return valve and a capillary

10   drug feed tube. There is a C spring, one end of which may rotate in a groove in the

rigid tube wall. The other is rigidly attached to an elongated mass such that rotation

of the mass extends the spring. There is a piston attached to the mass such that

contraction of the spring causes the piston to enter the hole in the rigid plastic tube

and impact on the silicone rubber liner. There is a detent such that the spring is bi-

15   stable. It may be extended manually to energise it. It may then be triggered by gentle

pressure on the skin. There is a retractor spring that retains the piston partially out of

the tube in the quiescent state to prevent compression set in the silicone liner and to

provide support to the liner under pressure from the associated syringe during drug

delivery.

20

Triggering the spring causes the spring energy to accelerate an attached mass. At

peak velocity, a piston attached to the mass penetrates the hole in the rigid tube wall

and impacts with the silicone liner to produce a high pressure transient. This transient

travels down the liquid drug filled rigid tube to the nozzle where it generates a high

25   velocity jet. This jet cuts a track through the skin. The outer surface surrounding the

nozzle keeps the entrance to the track open and in register with the nozzle so that the main dose may be fed through this hole in the skin using the piston in an attached syringe.

5   The silicone liner is a key element of the device. A silicone window within the wall of the rigid tube will tend to move inwards under the pressure of a piston. If the window is bonded, the bond will tend to tear under the high stresses entailed in forming a high pressure seal between the piston and hole. If the window is mechanically held, movement will be inevitable. The pressure generated at impact is

10   extremely high so the frictional force between the silicone window and hole in the rigid tube is very high and work done by the piston against this friction is very significant. Indeed, it may absorb 90% of the system energy. By using a liner within the tube, there is no possibility of the piston doing work against frictional loading between the silicone and the tube wall. The strain in the silicone rubber at the seal

15   between the piston and the rigid wall may be quite high. There are grades of silicone that extend 1000% before failure and this may be extended by inclusion of silicone oil in the rubber. An oil filled rubber will release oil under high strain and this free oil will form a lubrication film. Indeed, with a film of oil between the rubber and rigid walls, most of the silicone rubber will be under just isostatic pressure.

20

The non return valve within the injector serves three important functions. It is necessary to expel air from the injector system by flushing in the normal fashion. This is to prime the injector pump as well as preventing the formation of an air embolism within the patient. The pump volume is extremely small so the slightest

25   spring back of the piston after flushing will cause the injector to fill with air again.

The non return valve inhibits this. Biasing the valve shut will clearly enhance efficiency. Secondly, by ensuring that flow from the pump is unidirectional during jet generation, rather than bi-directional as in PCT/GB02/02633, more fluid is available for the jet and jet duration may last longer as there is no shunt from flow back into the

5   syringe reservoir. The third function is more subtle. If there is bi-directional flow out of the pump working volume, at the end of the jet generation phase there will be a very large negative pressure within the pump cavity. This will result in cavitation. Diffusion of dissolved air into this cavity will form a stable bubble that may compromise priming of the pump for a subsequent shot. With a non return valve, the

10   low pressure will simply open the valve and induce flow from the syringe reservoir. This not only inhibits cavitation but will marginally prolong the piercing jet flow.

The external profile of the nozzle is shaped to perform three important functions. There is a peripheral edge feature that generates a high contact pressure with the skin.

15   This acts as an effective hydraulic seal that prevents leakage of drug during delivery of the main dose. By arranging that the area of this seal is very small and the skin forms around a small radius edge, it may be ensured that the hydraulic seal pressure will always greatly exceed the drug delivery pressure from the syringe. In this manner, a wet shot is impossible.

20

The second function of the high pressure seal is to maintain alignment of the hole with the nozzle during drug delivery. The local high pressure of the seal at the edge implies a pressure gradient that will pump away any extraneous liquid on the skin that could act as a lubricant. The contact at the seal will be with dry skin therefore and

25   there will be a high coefficient of friction. This will effectively maintain registration

of the skin with the nozzle. Because the seal has comparable size to the nozzle effective alignment of nozzle and track will be maintained.

The third function is to keep the orifice of the track open under pressure.

5   Mechanically, the skin tends to act as a thick membrane. Depressing it locally with the injector will cause the outer surface to go into compression, so effectively sealing the entry to the track. By creating a saddle shaped outer surface to the nozzle, the outer surface of the skin may be locally placed in tension so that the orifice to the track is held open. A rectangular cross section is more effective than a gently curved

10 anticlastic form. This is yet more effective if the width of the channel increases with distance from the axis of the nozzle. The skin bulges into the rectangular channel which places the surface in tension. The skin may touch the roof of the channel to form a hydraulic seal and any trapped air is pumped into the quasi triangular spaces formed between the skin and the right angled corners of the channel. A 2:1 rectangle

15 may stretch the skin by 100% compared with 50% for a semicircular channel.

The spring performance is vital and quite subtle. The spring in PCT/GB02/02633 stores energy in tension. While this is very efficient on volume, it implies very thin spring members as energy storage capacity diminishes rapidly with additional bending

20 strain. Because of speed constraints, the size of the spring is limited. The total spring energy available was significantly limited. Within a given size constraint, a C spring may store a significantly larger amount of energy in pure bending strain. Further, by tapering the spring in either thickness or width, the maximum permissible surface strain can be maintained throughout most of the mass of the spring. The tip of the C

25 spring may point approximately in the direction of impact so the spring will be very

rigid to the compression load at impact and the momentum of the spring will

contribute to the impact loading.

While a C profile offers advantages, the spring profile may be J or L shaped or indeed

5   any arbitrary arcuate form. It is convenient to use two springs symmetrically disposed

about the rigid tube and mechanically joined at either end. It is found that it is

desirable to fabricate the spring as an injection moulded component and polyether

ether ketone [PEEK] is found to be the optimal polymer for this purpose.

10   The spring energy transforms to kinetic energy, but the load generated at impact

equals the rate of destruction of momentum. It is vital therefore that the mass of the

system is optimised to provide efficient energy transfer. By connecting the spring to a

mass which in turn connects to a piston, the energy match can be optimised. In

PCT/GB02/02633, the mass of the end thrust beams is constrained by speed and

15   pressure requirements, so there is very little scope for effective matching.

The mass attached to the C spring may be essentially triangular in form. If one apex

attaches to the spring, another may rotate in transverse groove in the outer wall of the

rigid tube, so that rotation of the mass extends and energises the spring. Continued

20   rotation will eventually reduce the spring length, so a stop just past maximum

extension provides a latch point. If the spring rotates toward the nozzle during

extension, pressure from the skin of the patient may return the spring through the

maximum extension point and initiate spontaneous collapse. In this manner, pressure

against the skin of the patient can trigger the formation of a piercing liquid jet. The

25   relative geometry of the nozzle and spring may determine that the nozzle is securely

located and sealed to the skin before triggering. Similarly the trigger load may be determined by the choice geometry.

The load mass rotates to energise the spring. The unattached end of the spring rotates
5   in a groove in the outer wall of the rigid tube and the spring ends rotate through a given angle on extension of the spring. With careful design, all these rotations may be matched so that there is no significant moment applied to the spring in the latched configuration.

10   Most silicone rubbers will creep under constant load especially if oil filled. If the piston remains fully inserted in the quiescent state, such creep would provide a much reduced displacement on the pumping stroke. An extension to the main spring may bear on the rigid tube in such a way that in the quiescent state, the piston is partly retracted from the rubber liner to prevent such creep occurring. If the piston is
15   maintained within the hole in the rigid tube, it may act as a support for the silicone liner when the main dose is fed by hydraulic pressure generated by the piston in the syringe. This retractor spring may be arranged to be low spring rate compared with the main spring, so that it does not significantly affect the impact mechanics.

20   The preferred embodiment is shown schematically in figures 1 to 5.

Figures 1abc show three orthogonal views of the injector assembly in the quiescent state.

Figure 2 shows the spring latched in the energised state

Figure 3 illustrates the rotational mechanics of the spring

25   Figure 4 shows a valve structure suitable for use with an ampoule

Figure 5 shows the saddle surface around the nozzle.

Figure 1 shows a rigid tube, 1, injection moulded in polysulphone. It comprises a

nozzle, 15, a shoulder, 2, in the bore, 10, a transverse hole, 3, through the rigid tube

5   wall, spring retaining grooves, 4 and 5 in the outer wall of the body, a latch stop, 6, a

saddle shaped surface, 13, around the nozzle, 15, a spring retaining channel, 14, and a

Luer taper fitting, 12.. There is a tubular silicone liner, 7, within the bore of the rigid

tube and an interference fit retaining plug, 8, which comprises one or more flats, 9,

that form in conjunction with the bore of the rigid tube, 10, capillary feed tubes, 11.

10   There are two springs, 20, joined at either end, 21, 22 to form a single unit with a

plane of symmetry through the tube axis. At the free end, 21, the spring bridge, 37,

connects to a tab, 23, which in turn bears on the retaining groove, 4. This tab permits

combining a bearing forward of the latch stop, 6, with a longer spring that extends

well behind the latch stop, 6. At the other end, 22, the springs join through a rigid

15   connection to one apex, 25, of the triangular mass, 24. A small piston, 26, is attached

near a second apex, 27, and the third apex, 28, bears in the retaining groove, 5. At the

tip of the spring structure, there is formed a retractor spring, 29, that bears on the

outer wall of the rigid tube.

20   The injector is assembled by inserting the slightly undersized silicone liner tube, 7,

into the bore, 10, of the rigid tube, 1, then inserting the oversize retaining plug, 8. The

retaining plug compresses the silicone to form a hydraulic seal against the shoulder, 2,

and the bore, 10, of the rigid tube, 1. The thickness of the silicone tube, 7, is such that

it seals the capillary tubes, 11, to form an effective non return valve, 46. The axial

25   compression in the silicone tube, 7, biases the valve shut. The geometry of this valve

is such that it may open at 0.1 bar pressure from the dispensing syringe, yet withstand in excess of 100MPa reverse pressure during the jet forming pressure transient. The silicone rubber is preferably a highly extensible medical grade filled with 20% silicone oil. As explained above, the oil may act as a lubricant during the high strains

5   of jet ejection. It will also inhibit possible bonding of the silicone to the plug or bore of the rigid tube.

The spring may be extended over a specially shaped former to ensure uniform strain then relaxed into position on the rigid tube. The lip on the groove, 5, ensures that the

10   grooves, 4 and 5, together with latch stop, 6, retain the spring thereafter.

Figure 2 shows the spring in the energised state. The reactions, 16, 17, from the grooves, 4 an 5, produce a couple that is balanced by a compensating couple from the groove, 18, and the latch stop, 19. This provides a stable trigger position.

15

Figure 3 illustrates the relative rotations in the spring. The C spring is represented by a heavy line, 30, in its initial state and, 31, in the energised state. The spring rotates through angle, 32, during energising. On extension, the angle subtended by the ends of the spring reduces from 33 to 34. The line 35 represents the upper surface of the

20   mass, 24. This rotates by 36 during energising. Clearly for the spring to be free of an applied moment when fully energised $36 = 32 + 33 - 34$. There are clearly sufficient unconstrained variables for this condition to be met.

Figure 4 shows the valve design for an ampoule fitting. The free silicone liner, 40, is

25   shown in axial section in figure 4a. It is a blind tube in which the blind end, 41, has a

conical cross section, 47. The blind end has two parallel off-axis transverse cuts, 42
and 43. Figure 4b shows the silicone liner within the rigid tube bore, 10, axially
compressed between an interference fit stainless steel capillary tube, 44, and the
shoulder, 2. There is a conical counterbore to the stainless steel capillary tube, 45.

5   The axial compression of the liner causes radial expansion of the blind end which
opens the two transverse cuts, 42, 43, to form valve outlet ports. The conical rubber
moulding, 47, is forced against the counterbore, 45, to provide a non-return valve seal,
46, which is biased closed.

10   Figure 5 shows the saddle profile, 50, around the nozzle, 15. Figure 5a shows the
arrangement in plan form and figure 5b in elevation. Figure 5c shows a section
through the plane of symmetry with the injector in use. The tips of the walls, 51, both
seal and locate the skin, 52. The skin bulges into the rectangular channel, 56, under
pressure and the surface goes into tension. At the centre of the channel, the skin seals

15   to the nozzle and any trapped air is pumped in the voids, 54, at either side. The jet
cuts a hole through the skin, 53. To relieve tensile strain, the entrance to the hole, 55,
stays open. It is found that operation is improved if the saddle channel broadens
with distance from the nozzle, 57.

20   In operation, a syringe bearing a Luer taper fitting is filled with liquid drug and is
fitted to the Luer fitting on the jet injector. The assembly is held vertical and syringe
is tapped in the usual manner to bring any air bubbles to the top of the system. The
air is flushed from the syringe and the injector by flushing with liquid drug by
displacing the piston in the syringe. The spring on the injector is then cocked

25   manually. The assembly is held by the syringe piston and in pressed against the skin

of the patient at the injection site. The nozzle seals against the skin of the patient and

localises the nozzle in relation to the skin. The spring is then triggered by the

pressure against the skin of the patient. This accelerates the triangular mass. The

piston attached to the mass penetrates the hole in the rigid tube and impacts on the

5   silicone liner. This creates a high hydraulic pressure of approximately 100 MPa

which propagates as a shock front down the rigid tube. At the nozzle, this pressure

wave generates a high speed jet of liquid drug which is travelling at approximately

Mach 2 in human flesh. The velocity rise time at the leading edge of this jet is

approximately 1-2 microseconds. The jet pierces the skin of the patient. The

10   boundary layer of liquid drug is of course stationary in contact with the skin. The

passage of the finite jet is therefore limited by the losses to the boundary layer. The

high speed leading edge with therefore penetrate the toughest of epidermis, but the

depth of penetration may be precisely engineered by the diameter of the nozzle

together with the energy and volume associated with the jet.

15

The main dose is then delivered through the track cut through the skin by the piston

travelling down the syringe.

The pressure of the nozzle on the skin will produce a radial compressive stress pattern

20   of approximately spherical symmetry. The compressive stress will collapse

capillaries leading radially from the track cut through the skin. As the stress will

decrease as approximately the inverse square of radius from the nozzle, the dose will

be delivered to the end of the track.